

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Akepox 2030 Component B**
- Article number: 10601, 10614, 10602, 10566, 10612, 10605, 10613, 10565, 10563, 10600, 10603, 10564, 10604, 10649

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy resin adhesive

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

+44 (171) 635 91 91
National Poison Inform. Centre
Medical Toxicology Unit
Avalonley Road
London SE14 5ER
Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Muta. 2 H341 Suspected of causing genetic defects.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 1)

· Hazard pictograms

GHS05 GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labelling:

Formaldehyde, polymer with 1,3-phenylenebis(methylamine) and phenol
m-phenylenebis(methylamine)
phenol
Benzyl alcohol

· Hazard statements

N-(3-(trimethoxysilyl)propyl)ethylenediamine
H332 Harmful if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P260 Do not breathe vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**· Results of PBT and vPvB assessment

· PBT: Not applicable.
· vPvB: Not applicable.

* **SECTION 3: Composition/information on ingredients**· **3.2 Chemical characterisation: Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 57214-10-5 NLP: 500-137-0	Formaldehyde, polymer with 1,3-phenylenebis(methylamine) and phenol Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	25-50%
-----------------------------------	---	--------

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 2)

CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-xxxx	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	12.5-25%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	<12.5%
CAS: 108-95-2 EINECS: 203-632-7 Index number: 604-001-00-2 Reg.nr.: 01-2119471329-32	phenol ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 ⚠ Muta. 2, H341; STOT RE 2, H373 ⚠ Skin Corr. 1B, H314	1-5%
	N-(3-(trimethoxysilyl)propyl)ethylenediamine ⚠ Eye Dam. 1, H318 ⚠ Skin Sens. 1, H317	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Call for a doctor immediately. Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness
Nausea
Allergic reactions

- Information for doctor: The symptoms of phenol based poisoning appearances are white coloured mouth scabs, shock condition, insensibility, bradycardia and renal dysfunction and damage of renal tissue. Appropriate therapy measures: Administration of an adequate volume of liquid, gastrolavage in application of carbo medicinalis, sodium sulphate with plenty of water, infusion of glucose solution (5%); measures against state of shock, hemodialysis.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released:
Carbon monoxide (CO)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 3)

- **5.3 Advice for firefighters**

- Protective equipment:

- Additional information

Nitrogen oxides (NOx)

Wear fully protective suit.

Wear self-contained respiratory protective device.

Mount respiratory protective device.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

- **6.2 Environmental precautions:**

- **6.3 Methods and material for containment and cleaning up:**

- **6.4 Reference to other sections**

Wear protective equipment. Keep unprotected persons away.

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

- Information about fire - and explosion protection:

- **7.2 Conditions for safe storage, including any incompatibilities**

- Storage:

- Requirements to be met by storerooms and receptacles:

- Information about storage in one common storage facility:

- Further information about storage conditions:

- Storage class:

- **7.3 Specific end use(s)**

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

No special requirements.

Not required.

Keep container tightly sealed.

8

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:

No further data; see item 7.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 4)

· 8.1 Control parameters· Ingredients with limit values that require monitoring at the workplace:**108-95-2 phenol**

WEL	Short-term value: 16 mg/m ³ , 4 ppm
	Long-term value: 7.8 mg/m ³ , 2 ppm
	Sk

· DNELs**57214-10-5 Formaldehyde, polymer with 1,3-phenylenebis(methylamine) and phenol**

Oral	DNEL (Kurzzeit-akut)	3.33 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	3.33 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	0.00385-2.8 mg/kg bw/day (ARB)
		0.000167-0.008 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	0.000385-0.28 mg/kg bw/day (ARB)
		0.000167-0.008 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2-6 mg/m ³ Air (ARB)

1477-55-0 m-phenylenebis(methylamine)

Dermal	DNEL (Langzeit-wiederholt)	0.33 mg/kg bw/day (ARB)
Inhalative	DNEL (Langzeit-wiederholt)	1.2 mg/m ³ Air (ARB)

108-95-2 phenol

Oral	DNEL (Langzeit-wiederholt)	0.4 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	0.4 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	8 mg/m ³ Air (ARB)
		1.32 mg/m ³ Air (BEV)

· PNECs**57214-10-5 Formaldehyde, polymer with 1,3-phenylenebis(methylamine) and phenol**

PNEC (wässrig)	30 mg/l (KA)
	0.002 mg/l (MW)
	0.02 mg/l (SW)
PNEC (fest)	0.0236 mg/kg Trockengew (BO)
	0.01 mg/kg Trockengew (MWS)
	0.1001 mg/kg Trockengew (SWS)

1477-55-0 m-phenylenebis(methylamine)

PNEC (wässrig)	0.0094 mg/l (MW)
	0.094 mg/l (SW)

108-95-2 phenol

PNEC (wässrig)	2.1 mg/l (KA)
	0.00077 mg/l (MW)
	0.0077 mg/l (SW)
PNEC (fest)	0.136 mg/kg Trockengew (BO)
	0.00915 mg/kg Trockengew (MWS)
	0.0915 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· 8.2 Exposure controls· Personal protective equipment:· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 5)

· Respiratory protection:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Short term filter device:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (<http://www.stoko.com>)

Skin protection recommendation for skin cleaning after product handling:

SLIG SPEZIAL (<http://www.stoko.com>)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (<http://www.stoko.com>)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level \leq 6, 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

Nitrile rubber, NBR

Dermatril (Art_No. 740, 741, 742)

Camatril (KCL, Art_No. 730, 731, 732, 733)

Chloroprene rubber, CR

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 6)

- Camapren (KCL, Art_No. 720, 722, 726)
- As protection from splashes gloves made of the following materials are suitable: Butyl rubber, BR
Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
 - Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
 - Eye protection:  Tightly sealed goggles
 - Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty

Colour: Grey

· Odour: Characteristic· pH-value: Not applicable

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 205°C

· Flash point: 101°C· Ignition temperature: 435°C· Auto-ignition temperature: Product is not selfigniting.· Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: 1.3 Vol %

Upper: 13.0 Vol %

· Vapour pressure at 20°C: 0.1 hPa· Density at 20°C: 1.5 g/cm³

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Viscosity:

Dynamic at 20°C: 80,000 mPas

Kinematic: Not determined.

· Solvent content:

Organic solvents: 4.0 %

Solids content: 56.9 %

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 7)

- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Strong exothermic reaction with acids.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Corrosive gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Harmful if inhaled.

• LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	>2,094 mg/kg
Dermal	LD50	>9,260 mg/kg
Inhalative	LC50/4 h	16.8 mg/l (rat)

57214-10-5 Formaldehyde, polymer with 1,3-phenylenebis(methylamine) and phenol

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,020 mg/kg (rat)

1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	930 mg/kg (rat)
	NOEL	150 mg/kg (rat)
Dermal	LD50	3,100 mg/kg (rabbit)
Inhalative	LC50/4 h	2.4 mg/l (rat)
	LC50/1h	3.89 mg/l (rat)

108-95-2 phenol

Oral	LD50	300 mg/kg (mouse)
		317 mg/kg (rat)
Dermal	LD50	630 mg/kg (rat)
Inhalative	LC50/4 h	316 mg/l (rat)
	LC50/8h	0.9 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Suspected of causing genetic defects.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 8)

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****57214-10-5 Formaldehyde, polymer with 1,3-phenylenebis(methylamine) and phenol**

EC50	491.3 mg/l (BES)
EC50/48h	29.8 mg/l (daphnia magna)
EC50/72h	20.4 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	25.9 mg/l (Oncorhynchus mykiss)

1477-55-0 m-phenylenebis(methylamine)

EC50/48h	15.2 mg/l (daphnia magna)
EC50/72h	12 mg/l (Scenedesmus subspicatus)
	20.3 mg/l (selenastrum capricornutum)
LC50/96h	>100 mg/l (Oncorhynchus mykiss)
	87.6 mg/l (Oryzias latipes)
	>100 mg/l (Zebrabärbling)

108-95-2 phenol

EC50/24h	21 mg/l (BO)
EC50/96h	61.1 mg/l (green alge)
EC50/48h	3.1 mg/l (daphnia magna)
LC50/96h	8.9 mg/l (Oncorhynchus mykiss)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· Additional ecological information:**· General notes:**

Do not allow product to reach ground water, water course or sewage system.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

· 12.5 Results of PBT and vPvB assessment**· PBT:** Not applicable.**· vPvB:** Not applicable.**· 12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****· 13.1 Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

· Uncleaned packaging:**· Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017



Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 9)

SECTION 14: Transport information

<ul style="list-style-type: none"> • 14.1 UN-Number • ADR, IMDG, IATA 	UN2735
<ul style="list-style-type: none"> • 14.2 UN proper shipping name • ADR • IMDG, IATA 	2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)) POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
<ul style="list-style-type: none"> • 14.3 Transport hazard class(es) • ADR 	8 (C7) Corrosive substances. 8
<ul style="list-style-type: none"> • IMDG, IATA 	8 Corrosive substances. 8
<ul style="list-style-type: none"> • 14.4 Packing group • ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> • 14.5 Environmental hazards: • Marine pollutant: 	No
<ul style="list-style-type: none"> • 14.6 Special precautions for user • Danger code (Kemler): • EMS Number: • Segregation groups • Stowage Category • Segregation Code 	Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG35 Stow "separated from" acids.
<ul style="list-style-type: none"> • 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> • Transport/Additional information: 	
<ul style="list-style-type: none"> • ADR • Limited quantities (LQ) • Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> • Transport category • Tunnel restriction code 	3 E
<ul style="list-style-type: none"> • IMDG • Limited quantities (LQ) • Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 10)

· <u>UN "Model Regulation":</u>	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE)), 8, III
---------------------------------	---

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Information about limitation of use: Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- VOC EU 180.9 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H341 Suspected of causing genetic defects.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
- Recommended restriction of use refer to Technical Data Sheet (TDS)
- Department issuing SDS: Laboratory
- Contact: Dieter Zimmermann
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2017

Version number 12

Revision: 08.08.2017

Trade name: Akepox 2030 Component B

(Contd. of page 11)

Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 2: Germ cell mutagenicity – Category 2
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous
version altered.

Adaptation in accordance with REACH directive 1907/2006/EC

GB